

**AQUOS<sup>®</sup>**

With screen sizes ranging from 32" to 45"<sup>\*1</sup>, the elegant AQUOS<sup>®</sup> D90U/D50U Series sets the standard for high performance combined with high style. The D90U/D50U Series utilizes the next generation of Sharp's proprietary Advanced Super View/Black TFT Panel with multipixel technology, providing high brightness (450 cd/m<sup>2</sup>), 1200:1 Contrast Ratio, 6ms response time and wide viewing angles (176°H x 176°V). The 45" and 37" models include Four-Wavelength Backlight System for enhanced color reproduction, as well as full HD spec 1920 x 1080 resolution. The D90U/D50U Series features a sleek titanium cabinet and the 45" and 37" models have detachable speakers. In addition, the included table stand easily removes for wall mounting applications. A full complement of digital interfaces distinguish the D90U/D50U Series: Dual HDMI, DVI-I for PC compatibility, dual DTVLink (1394), RS-232C and HD component video inputs. Optional Wall Mount Brackets are also available: AN-37AG2 (Tilting) and AN-LCGWF (Flat).

**Features:**

**Next-Generation 16:9 ASV LCD Panel** from Sharp's state-of-the-art Kameyama factory producing enhanced 1200:1 contrast ratio and 6ms response time.

**Four-Wavelength Backlight System** (45" and 37" models only) provides enhanced color reproduction with deeper, more vivid reds than previously possible.

**Multi-Pixel Technology** divides each pixel into two sections and adds an advanced driving system to provide 60% improved color reproduction at wide viewing angles.

**Wide Viewing Angles (176H° x 176V°)** Sharp's AQUOS viewing angles are so wide, you can view the TV clearly from anywhere in the room!

**High Brightness (450 cd/m<sup>2</sup>)** AQUOS Liquid Crystal Televisions are very bright. You can put them anywhere – even near windows, doors or other light sources – and the picture is still vivid.

**High Contrast Ratio (1200:1)** provides incredible images whether you're watching dark or bright scenes.

**Digital Interfaces** include dual HDMI inputs, DVI-I for PC compatibility, dual DTVLink (1394), RS-232C for custom installations and HD component video inputs.

**Full HD Spec** (45" and 37" models only) 1920 x 1080 resolution displays HDTV programs in 1080p with a true 16:9 aspect ratio.

**Specifications**

Model Number	LC-45D90U	LC-37D90U	LC-32D50U
Screen Size <sup>*1</sup>	45"	37"	32"
Panel Type	Active Matrix (a-si TFT) Advanced Super View LCD		
Pixel Resolution	1920 x 1080		1366 x 768
Brightness	450 cd/m <sup>2</sup>		
Lamp Life <sup>*2</sup>	60,000 hrs.		
Viewing Angles	176°H x 176°V		
Audio System	10W + 10W		
Tuning System	ATSC / QAM / NTSC		
Contrast Ratio	1200:1		
Aspect Ratio	16:9		
Quick Shoot Response Time	6ms		
Color Temperature	Selectable: 13000°K, 9500°K, 8000°K, 6500°K, 5000°K (values are approximate)		
View Modes	Sidebar, Smart Stretch, Stretch, Zoom, Dot by Dot (for PC), Normal (for PC)		
DVI-I Input	DVI-I x 1		
RS-232C Input	9-pin mini D-Sub x 1		
HDMI Input	HDMI x 2		
HD Component Input	Y/Pr/Pb x 2		
S-Video Input	4-pin DIN x 1		
Composite Video Input (A/V)	RCA x 3		
Audio Inputs	RCA L/R x 3		
Audio Outputs	Optical Digital Audio x 1		
DTVLink	1394 x 2		
Backlight	Four-Wavelength		Three-Wavelength
Limited Warranty <sup>*3</sup>	1 year parts and labor		
Cabinet Color	Titanium		
Speakers	Detachable		Fixed
Table Stand	Included		
Optional Wall Mount Brackets	AN-37AG2 (Tilting) AN-LCGWF (Flat)		
Power Consumption AC	TBD	TBD	TBD
TV Dimensions (w x h x d) (in inches)			
TV, Stand and Speakers	44-7/8 x 32-3/4 x 12-3/64	36-39/64 x 28-45/64 x 12-3/64	32-3/64 x 25-5/8 x 12-1/64
TV and Stand	44-7/8 x 32-3/4 x 12-3/64	36-39/64 x 28-45/64 x 12-3/64	—
TV and Speakers	44-7/8 x 30-7/16 x 5-5/64	36-39/64 x 26-9/64 x 4-51/64	32-3/64 x 23-17/64 x 4-7/8
TV only	44-7/8 x 27-21/64 x 5-5/64	36-39/64 x 23-1/32 x 4-51/64	—
TV Weight (in pounds)			
TV, Stand and Speakers	77.2	57.3	45.2
TV and Stand	TBD	TBD	—
TV and Speakers	TBD	TBD	TBD
TV only	TBD	TBD	—
UPC	074000363250	074000363267	074000363274

<sup>\*1</sup> Actual screen size 44-17/32" measured diagonally (45), 37-1/64" measured diagonally (37) and 31-1/2" measured diagonally (32).<sup>\*2</sup> The typical period of time after which the lamp's power output will have decreased by about half, given that the AQUOS is used continuously in a 77°F room under standard lighting and brightness conditions.<sup>\*3</sup> See warranty statement included in the product operation manual PDF download at [www.sharpusa.com](http://www.sharpusa.com).

Manufactured under license from BBE Sound, Inc. "BBE" and its designs are the registered trademarks of BBE Sound, Inc.

AQUOS and Sharp are registered trademarks of Sharp Corporation.

Product specifications and design are subject to change without notice.